

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.: MEDB000062S Revision no.: 1

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

## This is to certify:

that the A and "B" class fireproof windows and side scuttles

with type designation(s) A-30 WINDOW 1200 x 2200

# issued to C.C. Jensen Window A/S Svendborg, Denmark

is found to comply with the Implementing Regulation (EU) 2024/1975 for Item no. MED/3.25 (Row 1 of 1) according to the following requirements: IMO Res. MSC.5(48)-(IGC Code) 3, IMO MSC/Circ.1120, SOLAS 74 Reg. II-2/9.

Further details of the equipment and conditions for certification are given overleaf.

Date of issue: 2025-02-25 Expiry date: 2030-02-24

DNV local unit: Denmark CMC

Approval Engineer: Karolina Kusmider



Notified Body No.: 0575

for DNV AS

Digitally Signed By: Christine Mydlak-Röder

Christine Mydlak-Röder Head of Notified Body



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved

ND THE EN

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Form code: MED 2101.NOR



Certificate no.: **MEDB000062S** Revision no.: **1** 

## Product description

"A-30 Window 1200 x 2200"

composed of steel frame, incorporating a glass unit consisting of glass construction: 6 mm thick toughened glass ISO 614 (manufactured by Vetrotech saint-Gobain) + 4 mm thick fire layer + 6 mm thick toughened glass ISO 614 + 8 mm air space with steel distance profile + 10 mm thick toughened pressure glass ISO 614.

Total window thickness is 34mm.

The glass pane is supported by two Monolux supporting blocks 35 x 13 x 50 mm and is sealed with silicone rubber gasket Shore 50, 33/40A around the all four edges of glass pane.

Steel frame is fastened to the bulkhead using M6 x12 mm screws at c/c 73 mm.

For further details, see the drawings listed under Type Examination documentation below.

## **Application/Limitation**

The window is approved for installation in steel bulkheads of class A-30. Other applications are subject to case-by-case approval. Bulkhead surrounding the window to be insulated to A-60.

Maximum size of exposed fire technical glazing unit:1220 mm x 2220 mm (W x H).Maximum clear light size:1200 mm x 2200 mm (W x H).

Fire against 6 mm thick toughened glass (internal side).

The window has only been evaluated with respect to fire technical properties (e.g. strength requirements have not been considered). Arrangement and location of any window is subject to approval from relevant authorities in each case.

Each product is to be supplied with its manual for installation, use and maintenance.

## Type Examination documentation

Document No.	Rev.	Document type	Title	Date
PGA11006A	A	REPORT	Test Report from Danish Institute of Fire and Security Technology, Copenhagen, Denmark.	2017-07-19

#### **Tests carried out**

Tested according to IMO 2010 FTP Code part 3.

#### Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating and the MED Mark of Conformity (see first page).